


# A-Z Super Sealer

## Solvent-Borne Acrylic Sealer



**DESCRIPTION** • **A-Z Super Sealer** is a high-performance Ethyl Methacrylate resin, solvent borne, floor coating providing a deep penetrating, non-yellowing, scuff resistant finish. **A-Z Super Sealer** is available as a clear or colored solution and in gloss, matt, or flat finish.

**USES** • **A-Z Super Sealer** is used as a sealer and finishing coat for various colored and uncolored concrete surfaces, such as stamped concrete, chemically stained concrete, and exposed aggregate concrete; and for masonry surfaces, including interlock and porous brick. **A-Z Super Sealer** is appropriate for interior as well as exterior applications when the surface is properly textured or a non-slip additive is added to the sealer. **A-Z Super Sealer** may be pigmented and applied to uncolored concrete surfaces to add color to the surface. **A-Z Super Sealer** helps to improve the durability of concrete surfaces and reduces discoloration and staining caused by common spills such as food and oil. **A-Z Super Sealer** also helps to reduce surface degradation caused by chloride penetration and efflorescence and is therefore commonly used around swimming pools on textured surfaces.

### ADVANTAGES

- ✓ Beautifies the look of the surface and gives it a new appearance.
- ✓ Enhances the color of stamped concrete and brings out the antique and texture effects.
- ✓ Seals and dust-proofs hardened concrete, stone, brick, stamped concrete, exposed aggregate, mortar, and grout surfaces.
- ✓ Protects surfaces against stain caused by oil and food spills.
- ✓ Formulated for interior and exterior use.
- ✓ Non-yellowing and preserves the natural look of paving materials.
- ✓ Extends the life of the structure by protecting the substrate from liquid ingress damage.
- ✓ Available in matt, flat and gloss finishes.

**LIMITATIONS** • Do not apply to new concrete surfaces before they have been allowed to cure for a minimum of 28 days. Do not apply if ambient temperature is expected to drop below 3°C in the proceeding 24 hours. Do not apply if rain, dew, or water exposure is expected within 24 hours after application. Avoid application in direct sunlight and during high winds.

Do not apply on areas where hydrostatic pressure is possible. Apply in thin coats only; never apply heavily as the sealer may become slippery. **Not recommended** for pre-sealed or dense surfaces such as marble, glazed tile or granite. Care should

be taken when applying to dense surfaces or exterior untextured surfaces subject to water exposure to apply a non-slip coating or add a non-slip additive to the sealer before application. Check compatibility with coating on previously treated surfaces. Clear **A-Z Super Sealer** enhances the color of treaded surfaces, and will therefore slightly alter the natural appearance of treated surfaces. Not intended as a waterproofing membrane.

**COVERAGE** • Must be applied full strength, never dilute. Coverage rates depend on porosity and texture of the surface, method of application, and other surface and job conditions. Minimum two coats are recommended. Dominant rates of coverage are 10-15 m<sup>2</sup>/GL for the first coat and 15-20 m<sup>2</sup>/GL for the second coat.

**SURFACE PREPARATION** • All surfaces must be clean, free of grease, oil, dirt, wax, and other foreign matter. Cleaning agents may be used provided they are thoroughly rinsed from all surfaces before application of **A-Z Super Sealer** and are used in accordance with the manufacture's recommendations. In some cases, scraping and wire brushing of previously applied coatings, followed by sanding and/or power washing may be necessary. Allow surface to dry for at least 24 hours. Do not use soap or detergent for cleaning; residue may prevent the sealer from bonding to the surface.

**APPLICATION** • **DO NOT THIN**, apply full strength. Avoid application in direct sunlight, or during strong wind. On hot days, apply early in the day when temperatures are lower, and when the concrete surface is in the shade. For best results, apply material when surface temperature will remain between 12°C and 25°C for 8 hours after application. Mask or protect surrounding areas from spills and contact with product or equipment. Rope off working area, close to traffic, and remove surrounding vehicles.

After thorough preparation of the surface, **A-Z Super Sealer** can be applied by brush or roller. Use of a synthetic or nylon bristled brush is recommended. A 6 mm nap roller is recommended for smooth surfaces. For rough surface a 9 - 12 mm nap roller is preferred. Two applications of material are highly recommended, especially on unpainted and highly porous surfaces. Always apply in thin coats and maintain a wet edge. Allow 24-48 hours drying time between coats.

Do not allow foot traffic for 24 hours after final application. Area may be opened to heavy foot traffic after a minimum of 72 hours.



## A-Z Super Sealer Solvent-Borne Acrylic Sealer

---

**MAINTENANCE** • Treated surfaces should be inspected periodically for thin or traffic-worn areas. Reapply sealer as necessary.

---

**CLEANING** • Tools and equipment must be cleaned with an organic solvent.

---

**STORAGE & SHELF LIFE** • Product should be stored at 25°C in dry conditions away from direct sun light or freezing conditions. Shelf life is approximately 12 months from date of purchase in original unopened container under specified storage conditions.

---

**SAFETY PRECAUTIONS** • DANGER! FLAMABLE VAPOR AND LIQUID. Contains aromatic hydrocarbons. HARMFUL VAPORS. CAUSES EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY – harmful or fatal if swallowed.

---

Do not breath vapor or mist. May affect the brain and nervous system, causing dizziness or nausea. Causes nose and throat irritation. Use in a well ventilated area. Use a properly fitted organic vapor respirator (NIOSH TC-84A approved). Use goggles, protective clothing and vinyl gloves when handling. Keep away from sources of heat or ignition. FIRST AID: Eyes – Do not rub eyes, immediately flush with plenty of fresh water while holding eyelids apart. Skin – Wash with soap and water. Inhalation – Leave the area if experience difficulty breathing. Ingestion – Immediately give large amounts of water and induce vomiting; seek immediate medical attention.

---

**PACKAGING** • 1 and 5 gallon containers and 55 Gallon drum.

---

---

### Creative Concrete Concepts

PO Box 925794, Amman 1110, Jordan; Tel +962-6-487-4078, Fax +962-6-488-9133 • PO Box 91234, City of Industry, CA 91715-1234, USA; Tel +1-909-266-0709, Fax +1-909-266-0711 • PO Box 31017, Sharjah, UAE; Tel +971-6-532-1119, Fax +971-6-532-8833

---